20351









SIZE	E SEE NOTE 2 IDEAL	E SEE NOTE 2 TOL.	T SEE NOTE 2 IDEAL	T SEE NOTE 2 TOL.	I MIN.	P SEE NOTE 6	β	T.P.I.
63	2.320	+.017 -.018	2.444	+.017 -.018	1.828	2.062	5° 05′	1.50
66	2.433	+.017 -.018	2.557	+.017 -.018	1.937	2.175	4° 52′	1.50
70	2.591	+.017 -.018	2.715	+.017 -.018	2.093	2.333	4° 34′	1.50

1. THIS IS A TOP SEAL FINISH AND PROPER FUNCTION OF CLOSURE REQUIRES THAT THE SEALING SURFACE MUST BE SMOOTH AND FREE OF IRREGULARITIES THAT WOULD PREVENT A VACUUM SEAL BEING MADE, OR INTERFERE WITH ROTATION OF CLOSURE. VARIATION OF .015 FLAT SHOULD NOT EXCEED CURVATURE OF A .093 RADIUS.

2. PROPER FUNCTION OF CLOSURE REQUIRES THAT THE "T" AND "E" DIAMETERS BE AS LITTLE OUT OF ROUND AS POSSIBLE AND BE AS CLOSE TO "IDEAL" AS POSSIBLE. THE AVERAGE OF THE MAXIMUM AND MINIMUM DIAMETERS OF THE "T" AND "E" SHOULD ALSO BE AS CLOSE TO "IDEAL" AS POSSIBLE.

3. 'T' DIAMETER MUST BE MAINTAINED THROUGHOUT THREAD TRAVEL. REF. DEPTH .583

4. CONSTRUCTION IS IDENTICAL FOR ALL FOUR THREADS.

5. DOTTED CONTOUR IS OPTIONAL, BUT MUST CLEAR CAP LIMITS SHOWN BY CROSS-HATCHED AREA ABOVE .587 DIMENSION.

6. CROSS-HATCHED AREA SHOWS CONTOUR TO BE CLEARED BY THE TOP OF THE GLASS FINISH FOR CORRECT SEALING RESULTS.

7. IN ORDER TO PROVIDE CAM-OFF ACTION FOR CAP REMOVAL TOP SURFACE OF TWO OPPOSING THREADS FROM POINT 'X' UPWARD ALONG HELIX ANGLE SHOULD BE SMOOTH AND SUBSTANTIALLY FILLED.

8. 'β' IS HELIX ANGLE AT PITCH DIAMETER. THE CUTTER IS INCLINED AT 'β' ANGLE FOR ALL THREADS AND ALL CUTS.

9. TANGENT $\beta = \dfrac{\text{LEAD}}{\pi\ (\text{MEAN BETWEEN MEAN 'T' AND MEAN 'E'})}$

10. THIS FINISH IS IDENTICAL TO GPI 2030 EXCEPT FOR THE .215 INCREASE IN HEIGHT.

THIS OFFICIAL GLASS PACKAGING INSTITUTE PRINT CONSTITUTES ONE IN A SERIES OF VOLUNTARY STANDARDS INTENDED TO PROVIDE A BASIS FOR ACHIEVING COMPATABILITY AND INTERCHANGEABILITY BETWEEN MANUFACTURERS AND USERS OF GLASS CONTAINERS AND CLOSURES THEREFOR. THE USER SHOULD BE AWARE THAT OTHER CONTAINER AND CLOSURE DESIGNS MAY DIFFER FROM THIS VOLUNTARY STANDARD, AND IT IS THE USERS'S RESPONSIBILITY TO MAKE THE FINAL DETERMINATION AS TO DESIGN AND COMPATABILITY. GPI ASSUMES NO RESPONSIBILITY FOR EITHER THE USE OF OR INTERPRETATION OF THE STANDARD, FOR IT BEING CURRENT, OR FOR THE DETERMINATION WHETHER ANY PARTICULAR MANUFACTURER'S PRODUCT CONFORMS TO THE STANDARD. THIS DRAWING CONTAINS INFORMATION TAKEN FROM ONE OR MORE PRINTS OF THE GLASS PACKAGING INSTITUTE (GPI). GPI OWNS ALL RIGHT, TITLE AND INTEREST IN THE COPYRIGHTS TO THIS DRAWING AND TO THESE PRINTS. GPI REQUIRES THAT YOU NOT REPRODUCE THIS DRAWING FOR OR DISTRIBUTE THIS DRAWING TO ANY THIRD PARTY WITHOUT GPI'S WRITTEN CONSENT. ANY INQUIRIES OR SUGGESTIONS CONCERNING THIS STANDARD CAN BE ADDRESSED TO THE GLASS PACKAGING INSTITUTE, WASHINGTON D.C. AT WWW.GPI.ORG.

COPYRIGHT © GPI 1998,1999

Edward A. Grant, CHAIRMAN	PRINTED AND DISTRIBUTED AS A VOLUNTARY STANDARD BY GLASS PACKAGING INSTITUTE, COMMITTEE ON DESIGN AND SPECIFICATIONS	APPROVED FOR PUBLICATION 02-05-99	SUPERSEDES DWG. NO. 20350
	GLASS FINISH NUMBER 2035	GPI DWG. NO. 20351	

TOP SEAL VACUUM LUG DEEP FINISH, SIZES 63,66 & 70 (4 LEADS)